

Area Flash Light SQ2216FL - Technical data



- LED Area Light for flash operation
- active light field 220 mm x 160 mm
- 588 high performance 5 mm LEDs
- applicable as a clear, diffused, polarised, focusing incident illumination or as a transmitted illumination
- integrated illumination controller
- brightness can be regulated internally (potentiometer) or externally with a VC analogue input
- adjustable flash times up to 220 µs
- different trigger modes
- robust industrial model, Aluminium casing, IP40
- 150 mm cable with an M16 12-pin plug
- drag chain connection cable with an M16 12-pin socket in different lengths available as accessory ↻ *please note page 211 of the main product catalogue*

LIFETIME
75.000h+

x=0,31
y=0,31

470nm

525nm

625nm

870nm

Strobe / Flash

CONTROLLER
INSIDE

With the following table you can assemble your desired type of lighting:*

* A detailed product key explanation can be found on ↻ [Page 4](#) of the main product catalogue.

Available illumination variants					
Model	Diffusing panel	Illumination colour	Brightness regulation	Trigger	Flash time
SQ2216FL	ALK ALD DL	R IR870 W B G	Potentiometer, optional VC	SPS TTL	100 220

Operation mode	Flash	
Operation voltage	19...30 V DC	wide range voltage input
Max. current	3,2 A	at 24 V
Trigger modes	TTL / SPS	TTL: rising slope at trigger input, min. 2,8 V DC, max. 30 V DC SPS: rising slope at trigger input, min. 15 V DC, max. 30 V DC
Flash times	10 - 100 µs / 20 - 220 µs	adjustable with potentiometer, max. flash frequency 100 Hz or 35 Hz
Brightness regulation	Potentiometer / VC	Potentiometer: 0...100 % (deactivated with VC - models) or VC: 0...100 % when connected to a voltage of 2...10 V DC on the VC analogue input (potentiometer deactivated)
Ambient temperature	5 - 45 °C / 37 - 113 °F	non-condensing
Weight	1,8 kg	
Protection class	IP 40	
Connection	M16 12-pin plug	150 mm drag chain cable with an M16 12-pin plug, IP67

Price list: page 298 of the main product catalogue

Pin arrangement M16 plug			
A+K	white	GND	GND Operation voltage
B+L	brown	U _B	Operation voltage
C	green	NC	NC
D	yellow	VC	Brightness regulation 2...10 V DC
E	grey	NC	NC
F	pink	+Trigger SPS / TTL	SPS >15 V / TTL >3 V, rising slope
G	blue	GND Trigger	GND trigger circuit
H	Shield	Shield	Shield connection
J	nc	NC	NC
M	nc	NC	NC

Area Flash Light SQ2216FL - Technical drawing

