

Area Light SQCB2216 - Technical data



- LED Area Light with camera hole for continuous / switch operation
- active light field 220 mm x 160 mm x D40 mm
- 564 high performance 5 mm LEDs
- applicable as a clear or polarised incident illumination
- integrated illumination controller
- brightness can be regulated internally (potentiometer) or externally with a VC analogue input
- robust industrial model, Aluminium casing, IP40
- 150 mm cable with an M16 12-pin plug
- drag chain connection cable with an M16 12-pin socket in different lengths available as accessory ↪ [please note page 211 of the main product catalogue](#)

LIFETIME
75.000h+

x=0,31
 y=0,31

470nm

525nm

625nm

870nm

CONTINUOUS

SWITCH

CONTROLLER
 INSIDE



Price list: [page 302 of the main product catalogue](#)

With the following table you can assemble your desired type of lighting:*

* A detailed product key explanation can be found on [Page 4](#) of the main product catalogue.


Available illumination variants

Model	Diffusing panel	Illumination colour	Brightness regulation
SQCB2216	ALK ALD DL	R IR870 W B G	Potentiometer, optional VC

Operation mode	Continuous / switch	VC analogue input with up to 30 V DC
Operation voltage	19...30 V DC	wide range voltage input
Max. current	2,0 A	at 24 V
Brightness regulation	Potentiometer / VC	Potentiometer: 0...100 % (deactivated with VC - models) or VC: 0...100 % when connected to a voltage of 1...10 V DC on the VC analogue input (potentiometer deactivated)
Switching (Load-free)	20ms on time up to continuous operation, VC-voltage 10-30 VDC	Switching rate max. 10 Hz; brightness regulation via VC-input not possible (potentiometer must be deactivated)
Ambient temperature	5 - 45 °C / 37 - 113 °F	non-condensing
Weight	1,9 kg	
Protection class	IP 40	
Connection	M16 12-pin plug	150 mm drag chain cable with an M16 12-pin plug, IP67

Pin arrangement M16 plug

A+K	white	GND	GND Operation voltage
B+K	brown	U _b	Operation voltage
C	green	NC	NC
D	yellow	VC	Brightness regulation 1...10 V DC
E	grey	NC	NC
F	pink	NC	NC
G	blue	NC	NC
H	Shield	Shield	Shield connection
J	nc	NC	NC
M	nc	NC	NC



Area Light SQCB2216 - Technical drawing

