

Ring Light CRC CD50 - Technical data



- LED Ring Light for continuous / switch operation
- light field diameter 54 mm - 73 mm
- extremely flat construction height
- 78 high performance SMD LEDs
- applicable as a clear incident illumination
- an external illumination controller PLC2 necessary
 ↪ [please note page 204 of the main product catalogue](#)
- brightness can be regulated with a external controller
- robust industrial model, Aluminium casing, IP40
- 1,5 m drag chain cable with M16 plug for connecting to the PLC2

LIFETIME
75.000h+

x=0,31
y=0,31

470nm

525nm

625nm

CONTINUOUS

SWITCH

~~CONTROLLER INSIDE~~



Price list: page 321 of the main product catalogue

With the following table you can assemble your desired type of lighting:*

* A detailed product key explanation can be found on ↪ [Page 4](#) of the main product catalogue.

Available illumination variants

Model	Diffusing panel	Illumination colour	Brightness regulation
CRC CD50	ALK ALD POL	R W B G	↪ observe controller PLC2

Operation mode	Continuous / switch	external controller PLC2 necessary
Operation voltage	↪ observe controller PLC2	wide range voltage input
Max. current	0,3 A	at 24 V
Brightness regulation	Potentiometer / VC	adjustable with external controller PLC2
Switching (Load-free)	VC	↪ observe controller PLC2
Ambient temperature	5 - 45 °C / 37 - 113 °F	non-condensing
Weight	0,15 kg	
Protection class	IP 40	
Connection cable	1,5 m cable	drag chain cable, bending radius min. 72 mm, Lumberg 6-pin plug, for connecting to the controller PLC2

Ring Light CRC CD50 - Technical drawing

