

## Spot L6 - Technical data



- LED Spot for continuous / switch operation
- 6 high performance 5 mm LEDs
- integrated illumination controller
- no brightness regulation
- robust industrial model, Aluminium casing, IP40
- 1,5 m connection cable with open end

With the following table you can assemble your desired type of lighting:\*

\* A detailed product key explanation can be found on [Page 4](#) of the main product catalogue.

Available illumination variants		
Model	Diffusing panel	Illumination colour
Spot L6	-	R IR870 W B G

<b>Operation mode</b>	Continuous / switch	switch works over the operation voltage
<b>Operation voltage</b>	24 V DC	
<b>Max. current</b>	0,05 A	at 24 V
<b>Brightness regulation</b>	no	
<b>Ambient temperature</b>	5 - 45 °C / 37 - 113 °F	non-condensing
<b>Weight</b>	0,03 kg	
<b>Protection class</b>	IP 40	
<b>Connection cable</b>	1,5 m cable	open end

Cable configuration		
<b>brown</b>	+24 V DC	+ operation voltage (max. 30 V)
<b>white</b>	GND	GND operation voltage

**LIFETIME**  
75.000h+

x=0,31  
y=0,31

470nm

525nm

625nm

870nm

CONTINUOUS

SWITCH

CONTROLLER  
INSIDE



*Price list: page 376 of the main product catalogue*

## Spot L6 - Technical drawing

