

LED Bar Light LB250 - Technical data



- LED Bar Light for continuous / switch operation
- 20 high performance Power LEDs / 10 high performance UV LEDs
- applicable as incident illumination, suited for matrix and line camera applications
- different lenses available as accessories
- integrated illumination controller
- brightness can be regulated internally (potentiometer) or externally with a VC analogue input
- robust industrial model, Aluminium casing, IP67
- 150 mm cable with an M16 12-pin plug
- drag chain connection cable with an M16 12-pin socket in different lengths available as accessory [↩ please note page 211 of the main product catalogue](#)

LIFETIME
50.000h+

x=0,31
y=0,31

365nm

400nm

470nm

528nm

625nm

850nm

CONTINUOUS

SWITCH



CONTROLLER INSIDE



Price list: page 373 of the main product catalogue

With the following table you can assemble your desired type of lighting:*

* A detailed product key explanation can be found on [Page 4](#) of the main product catalogue.

Available illumination variants


Model	Radiation angles (°) Ancillary lenses	Illumination colour
LB250	16° 23° 44° 48x19°	R W B G IR850
	12° , 18° , 27° , square housing	UV365 UV400

Operation mode	Continuous / switch	load-free switching via TTL and SPS input
Operation voltage	19...30 V DC	wide range voltage input
Max. current	1,2 A	at 24 V
Brightness regulation	Potentiometer / VC	Potentiometer: 0...100 % or VC: 0 – 100 % with VC-analogue input 1...10 V DC VC-voltage > 1 VDC -> potentiometer deactivated automatically, recommendation: turn the potentiometer fully anti-clockwise (left)
Switch operation	TTL PLC	load-free, opto isolated switching inputs TTL - High = 3 – 30 V DC SPS – High = 15 – 30 V DC connect the GND trigger switching period is controlled via trigger signal
Continuous operation		The trigger input need a permanent high signal (e.g. connection of the operating voltage) for continuous mode connect the GND trigger
Ambient temperature	5 - 45 °C / 37 - 113 °F	
Weight	0,75 kg	
Protection class	IP67	
Connection	M16 12-pin plug	150 mm drag chain cable with an M16 12-pin plug, IP67

Pin arrangement M16 plug

A+K	white	GND	GND Operation voltage	
B+L	brown	U _B	Operation voltage	
C	green	NC	NC	
D	yellow	VC	Brightness regulation 1...10 V DC	
E	grey	+ ON / OFF TTL	Switching input, TTL > 3 V DC	
F	pink	+ ON / OFF SPS	Switching input, SPS > 15 V DC	
G	blue	GND ON / OFF	GND switch circuit	
H	Shield	Shield	Shield connection	
J	nc	NC	NC	
M	nc	NC	NC	

LED Bar Light LB250 (except UV) - Technical drawing



LED Bar Light LB250-UV - Technical drawing

