

Spot5W - Technical data



- High Power LED Spot for continuous / switch operation
- 1 high performance 5 Watt LED
- adjustable optic for focused or a very homogeneous illumination
 (WD: 100 mm Ø: 25...120 mm)
 (WD: 250 mm Ø: 50...250 mm)
- integrated illumination controller
- brightness can be regulated internally (potentiometer) or externally with a VC analogue input
- robust industrial model, Aluminium casing, IP40
- M30,5 x 0,5 filter thread
- 150 mm cable with an M16 12-pin plug
- drag chain connection cable with an M16 12-pin socket in different lengths available as accessory ↪ [please note page 211 of the main product catalogue](#)

With the following table you can assemble your desired type of lighting:*

* A detailed product key explanation can be found on ↪ [Page 4](#) of the main product catalogue.


Available illumination variants

Model	Illumination colour	Brightness regulation
Spot5W	R IR850 W B G UV365 UV400	Potentiometer, optional VC

Operation mode	Continuous / switch	load-free switching via TTL and SPS input
Operation voltage	19...30 V DC	wide range voltage input
Max. current	0,2 A	at 24 V
Brightness regulation	Potentiometer / VC	Potentiometer: 0...100 % or VC: 0 – 100 % with VC-analogue input 1...10 V DC VC-voltage > 1 VDC -> potentiometer deactivated automatically, recommendation: turn the potentiometer fully anti-clockwise (left)
Switch operation	TTL PLC	load-free, opto isolated switching inputs TTL - High = 3 – 30 V DC SPS – High = 15 – 30 V DC connect the GND trigger switching period is controlled via trigger signal
Continuous operation		The trigger input need a permanent high signal (e.g. connection of the operating voltage) for continuous mode connect the GND trigger
Ambient temperature	5 - 45 °C / 37 - 113 °F	non-condensing
Weight	0,15 kg	
Protection class	IP 40	
Connection	M16 12-pin plug	150 mm drag chain cable with an M16 12-pin plug, IP67

Pin arrangement M16 plug

A+K	white	GND	GND Operation voltage
B+L	brown	U _B	Operation voltage
C	green	NC	NC
D	yellow	VC	Brightness regulation 1...10 V DC
E	grey	+ ON / OFF TTL	Switching input, TTL > 3 V DC
F	pink	+ ON / OFF SPS	Switching input, SPS > 15 V DC
G	blue	GND ON / OFF	GND switch circuit
H	Shield	Shield	Shield connection
J	nc	NC	NC
M	nc	NC	NC



LIFETIME
75.000h+

x=0,31
y=0,31

365nm

400nm

470nm

528nm

625nm

850nm

CONTINUOUS

SWITCH

CONTROLLER
INSIDE



Price list: page 381 of the main product catalogue



Mounting solution:
starting on page 221 of the main product catalogue

Spot5W - Technical drawing

