

Connecting cables

| Article No | Description | Price (€) |
|--------------------|---|---------------|
| 115.0000.01 | LUMIMAX® Connecting Cable 1,0 m length 1,0 m; with M16 12-pin plug (female); suitable for drag chains and robotic (1 million cycles with +/- 90° torsion); IP67 | 45,00 |
| 115.0000.02 | LUMIMAX® Connecting Cable 2,5 m length 2,5 m; with M16 12-pin plug (female); suitable for drag chains and robotic (1 million cycles with +/- 90° torsion); IP67 | 51,75 |
| 115.0000.03 | LUMIMAX® Connecting Cable 5,0 m length 5,0 m; with M16 12-pin plug (female); suitable for drag chains and robotic (1 million cycles with +/- 90° torsion); IP67 | 63,00 |
| 115.0000.04 | LUMIMAX® Connecting Cable 7,5 m length 7,5 m; with M16 12-pin plug (female); suitable for drag chains and robotic (1 million cycles with +/- 90° torsion); IP67 | 74,25 |
| 115.0000.05 | LUMIMAX® Connecting Cable 10,0 m length 10,0 m; with M16 12-pin plug (female); suitable for drag chains and robotic (1 million cycles with +/- 90° torsion); IP67 | 85,50 |
| 115.0000.06 | LUMIMAX® Connecting Cable 15,0 m length 15,0 m; with M16 12-pin plug (female); suitable for drag chains and robotic (1 million cycles with +/- 90° torsion); IP67 | 108,00 |
| 115.0000.10 | LUMIMAX® Connecting Cable 20,0 m length 20,0 m; with M16 12-pin plug (female); suitable for drag chains and robotic (1 million cycles with +/- 90° torsion); IP67 | 135,00 |
| 115.0000.11 | LUMIMAX® Connecting Cable 25,0 m length 25,0 m; with M16 12-pin plug (female); suitable for drag chains and robotic (1 million cycles with +/- 90° torsion); IP67 | 155,00 |
| 115.0000.12 | LUMIMAX® Connecting Cable 30,0 m length 30,0 m; with M16 12-pin plug (female); suitable for drag chains and robotic (1 million cycles with +/- 90° torsion); IP67 | 180,00 |
| 115.0002.01 | LUMIMAX® T1-Adapter cable IS5x enables a direct connection of LUMIMAX® lights with flash or switching operation to Cognex InSight 5x; maximal 10m camera cable; except: all lights, which need an external controller, as well as SQ2216/FL, SQCB2216/FL, LG3020/FL, LGCB3020/FL, LG4030/FL, LGCB4030/FL, LB500/FL; IP67 | 130,00 |
| 115.0002.02 | LUMIMAX® T1-Adapter cable IS7x enables a direct connection of LUMIMAX® lights with flash or switching operation to Cognex In-Sight® 7x; maximal 10m camera cable; except: all lights, which need an external controller, as well as SQ2216/FL, SQCB2216/FL, LG3020/FL, LGCB3020/FL, LG4030/FL, LGCB4030/FL, LB500/FL; IP67 | 130,00 |
| 115.0002.03 | LUMIMAX® T1-Adapter cable VeriSens XC enables a direct connection of LUMIMAX® lights with flash or switching operation to Baumer VeriSens® XC; maximal 10m camera cable; except: all lights, which need an external controller, as well as SQ2216/FL, SQCB2216/FL, LG3020/FL, LGCB3020/FL, LG4030/FL, LGCB4030/FL, LB500/FL; IP67 | 130,00 |
| 115.0002.04 | LUMIMAX® T1-Adapter cable MV440 enables a direct connection of LUMIMAX® lights with flash or switching operation to SIMATIC MV440; maximal 10m camera cable; except: all lights, which need an external controller, as well as SQ2216/FL, SQCB2216/FL, LG3020/FL, LGCB3020/FL, LG4030/FL, LGCB4030/FL, LB500/FL; IP67 | 130,00 |
| 115.0003.01 | LUMIMAX® extension cable 1m length 1,0 m; assembled at end with M16 12pin female and male plug; suitable for drag chains and robotic (1 million cycles with +/- 90° torsion); IP67 | 74,50 |
| 115.0003.02 | LUMIMAX® extension cable 15 m length 15,0 m; assembled at end with M16 12pin female and male plug; suitable for drag chains and robotic (1 million cycles with +/- 90° torsion); IP67 | 146,85 |
| 115.0003.03 | LUMIMAX® extension cable; 3 m length 3,0m; assembled at end with M16 12pin male and female connector; suitable for drag chains and robotic (1 million cycles with +/- 90° torsion); IP67 | 90,00 |
| 115.0003.04 | LUMIMAX® extension cable 2 m length 2,0 m; assembled at both end with M16 12pin female and male plug; suitable for drag chains and robotic (1 million cycles with +/- 90° torsion); IP67 | 83,90 |
| 115.0003.05 | LUMIMAX® extension cable; 5 m length 5,0 m; assembled at end with M16 12pin male and female connector; suitable for drag chains and robotic (1 million cycles with +/- 90° torsion); IP67 | 98,40 |
| 115.0003.06 | LUMIMAX® extension cable; 10 m length 10,0 m; assembled at end with M16 12pin male and female connector; suitable for drag chains and robotic (1 million cycles with +/- 90° torsion); IP67 | 122,60 |
| 115.0003.07 | LUMIMAX® extension cable 0,75 m length 0,75 m; assembled at end with M16 12pin female and male plug; suitable for drag chains and robotic (1 million cycles with +/- 90° torsion); IP67 | 74,50 |
| 115.0003.08 | LUMIMAX® extension cable 0,5 m length 0,5m; assembled at end with M16 12pin male and female connector; suitable for drag chains and robotic (1 million cycles with +/- 90° torsion); IP67 | 74,50 |
| 115.0003.09 | LUMIMAX® extension cable M8 3pin length 5,0 m; assembled at end with M8 3pin female and male plug | 55,00 |
| 115.0003.10 | LUMIMAX® extension cable 15 m length 15,0 m; assembled at end with M16 12pin female and male plug; suitable for drag chains and robotic (1 million cycles with +/- 90° torsion); IP67 | 171,05 |
| 115.0006.01 | VS-4xM8/3pin-1xM12/12pin Distribution system for max 4 lights with 3pin M8 plug (male), IP67 | 89,00 |
| 115.0007.01 | Connecting cable M12 12pin; 2 m Length 2 m; with M12 12-pin plug (female); suitable for drag chains; PUR cable; IP67 | 56,00 |
| 115.0007.02 | Connecting cable M12 12pin; 5 m Length 5 m; with M12 12-pin plug (female); suitable for drag chains; PUR cable; IP67 | 66,00 |
| 115.0007.03 | Connecting cable M12 12pin; 10 m Length 10 m; with M12 12-pin plug (female); suitable for drag chains; PUR cable; IP67 | 87,00 |
| 115.0007.04 | Connecting cable M12 12pin; 15 m Length 15 m; with M12 12-pin plug (female); suitable for drag chains; PUR cable; IP67 | 106,00 |
| 115.0007.41 | Connecting cable M12 4pin; 2 m Length 2 m; with M12 4-pin plug (female); suitable for drag chains; PUR cable; IP67 | 20,00 |
| 115.0007.42 | Connecting cable M12 4pin; 5m Length 5 m; with M12 4-pin plug (female); suitable for drag chains; PUR cable; IP67 | 25,00 |



Connecting cables

| Article No | Description | Price (€) |
|--|---------------------------------------|---------------|
| 115.0007.43 Length 10m; with M12 4-pin plug (female); suitable for drag chains; PUR cable; IP67 | Connecting cable M12 4pin; 10m | 40,00 |
| 115.0007.44 Length 20 m; with M12 4-pin plug (female); suitable for drag chains; PUR cable; IP67 | Connecting cable M12 4pin; 20m | 75,00 |
| 115.0007.45 Length 30m; with M12 4-pin plug (female); suitable for drag chains; PUR cable; IP67 | Connecting cable M12 4pin; 30m | 110,00 |
| 115.0007.46 length 20m; with 12 4-pin plug (female); suitable for drag chains; PUR cable; IP67 | Connecting cable M12 4pin; 15m | 60,00 |
| 115.0008.31 length 2,0 m; with M8 3-pin plug (female); suitable for drag chains; PUR cable; IP67 | Connecting Cable M8 3pin; 2 m | 27,00 |
| 115.0008.32 length 5,0 m; with M8 3-pin plug (female); suitable for drag chains; PUR cable; IP67 | Connecting cable M8 3pin; 5 m | 36,00 |
| 115.0008.33 length 10,0 m; with M8 3-pin plug (female); suitable for drag chains; PUR cable; IP67 | Connecting cable M8 3pin; 10 m | 49,00 |
| 115.0008.34 length 20,0 m; with M8 3-pin plug (female); suitable for drag chains; PUR cable; IP67 | Connecting cable M8 3pin; 20 m | 86,00 |
| 115.0008.51 length 2,0 m; with M8 5-pin plug (female); for flash controller FLC1; suitable for drag chains; PUR cable; IP67 | Connecting Cable M8 5pin; 2 m | 39,00 |
| 115.0008.52 length 5,0 m; with M8 5-pin plug (female); for flash controller FLC1; suitable for drag chains; PUR cable; IP67 | Connecting Cable M8 5pin; 5 m | 51,00 |
| 115.0008.53 length 10,0 m; with M8 5-pin plug (female); for flash controller FLC1; suitable for drag chains; PUR cable; IP67 | Connecting Cable M8 5pin; 10 m | 69,00 |

